



NAVID ZAR CHIMI Ind. Co.
Polypropylene Manufacturer



❖ Parslen ZH515MA

Parslen ZH515MA is a Polypropylene homopolymer developed for the high speed extrusion of transparent cast and blown film.

🕒 Product Description:

- Parslen ZH515MA is formulated with an effective slip and antiblocking package and is suitable for the extrusion of low thickness films and can be used for films from 15 to 150 μm .
- Main characteristics of Parslen ZH515MA are faster processing, high transparency and high gloss.

🕒 Application:

- Because of their high transparency and good handling properties, films made with Parslen ZH515MA are used for the production of shopping bags and packaging for snacks, bakery products, books, blankets, hosiery and shirts. Another major application is the production of stationery folders. Twines and ropes.



Typical Properties [a,b]	Method	Unit	Value(a)	Tolerance
Melt flow rate(230 ° C, 2.16 Kg)	ASTM D 1238	gr/10 min	9	± 2
Vicat softening point (9.8 N)	ASTM D 1525	° C	151	± 5
H.D.T. (0.46 MPa)	ASTM D 648	° C	95	± 8
Flexural modulus	ASTM D 790	MPa	1200	± 120
Tensile strength at yield	ASTM D 638	MPa	32	± 5
Elongation at yield	ASTM D 638	%	12	-2
Izod impact strength(notched) at 23° C	ASTM D 256	J/m	37	± 4
Rockwell hardness [R – B Scale]	ASTM D 785	R – B	100	+20
Haze	MTM 17031	%	2	± 0.5
Gloss	MTM 17021	%	80	± 5

a) Values shown are averages and are not to be considered as exact product specifications.

b) All specimens are prepared by injection molding. (Last revised 31, July 2008)



Parslen ZH515MA is suitable for food contact.