



Jampilen EPX-3130UV

Heterophasic copolymer - Trial

JAMPILen Polypropylene

Description:

Jampilen EPX-3130UV is a non-filled polypropylene copolymer for injection molding with very high impact strength. The product has good U.V. resistance designed for outdoor applications. This grade is used for production of automotive parts, and compounding.

Processing Method:

Injection molding
Compounding

Features:

Very high impact strength especially at low temperatures
Good U.V. resistance
Good processability
Heterophasic copolymer

Typical Applications:

Automotive bumpers
Outdoor applications
Technical articles

TYPICAL PROPERTIES	VALUE	UNIT	METHOD
Physical			
Melt Flow Rate (230 °C, 2.16kg)	10.5	g/10min	ASTM D1238
Density	0.9	g/cm ³	ASTM D1505
Mechanical			
Flexural Modulus	900	MPa	ASTM D790
Tensile Strength at Yield	19	MPa	ASTM D638
Tensile Elongation at Yield	6	%	ASTM D638
Izod Impact Strength (notched) at 23 °C	500	J/m	ASTM D256
Izod Impact Strength (notched) at -20 °C	100	J/m	ASTM D256
Thermal			
H.D.T. (0.46 Mpa)	75	°C	ASTM D648
Accelerated oven ageing in air at 150 °C	360	hour	ASTM D3012

No. 5, North-Falamak St., Eyyanak Blvd., Farahzadi Blvd., Shahrak-e-Qods., Tehran, 1467715171, Iran.
Tel: +9821-84286, Fax: +9821-88563100
Email: info@jppc.ir
www.jppc.ir

This data and information is considered to be correct and offered in good faith as a guide. But we do not warrant or otherwise guarantee the merchantability, fitness for a particular purpose or suitability of this information, products or processes described.